

DAVIS ROPE AND CABLE ASSEMBLY

IMPORTANT INFO REGARDING YOUR ROPE

Thanks so much for your order. If you are fully satisfied with this transaction, the quality and price, please “spread the word” about us as that is the best help we can get to continue our quality, low pricing (as of today, we do not see lower pricing available for this product) and our devotion to *Customer Satisfaction*.

It is **VERY IMPORTANT** that if you cut the rope that you SEAL the cuts properly. If not, the outer braid jacket will creep back up the rope revealing the inner braided core. This can cause several problems, not to mention if the rope happens to be a stealth color, then usually the inner core is bright white. It is not difficult to properly seal a cut made in the rope and usually it only takes less than 30 seconds per seal.

CUTTING & Sealing Procedure: First tightly apply a piece of scotch tape or electrical tape twice over on the spot you want to cut. Using a very sharp single edged razor, or box cutter, cut at the midpoint of the tape. Using a candle, match, lighter or burner igniter: touch the taped end of the rope into the TOP TIP OF THE FLAME for long enough to create a molten bead of rope material. Then remove from the flame and pull the molten end of the rope thru a cloth rag (not paper towel) . This will taper out the molten material so there is both a thorough, concentric, molten seal as well as not leaving a “bulge” at the rope end that would increase the diameter at that point, possibly causing thru pulley restriction and/or knot tying interference.

CAUTION: Be very careful with the rag so that you DO NOT TOUCH THE HOT END OF THE ROPE, or any molten material...it will burn you!! USE SAFETY GLOVES. It will take **up to 30 seconds for the hot rope to cool off** BEFORE YOU TOUCH IT. Also, after use, locate the rag that you have used in a metal bucket or glass etc. as it MAY FLAME UP, or burn adjacent material.

We provide the above information as helpful hints to save you time and to perfect the end product of your cutting and sealing. Davis Rope and Cable Assembly Co. assumes no responsibility for damage to property or injury to persons, pets, animals, or any and all damages and injuries that may result by an end user in the process of cutting, sealing or any form of use of rope products. It is the responsibility of the end user also to assess and regulate load factors applied to this rope during its use and/or continued application.

Please keep us in mind also for your cable assembly needs. We will assemble ANY RF connector on to ANY type coaxial cable. Also, we supply all types of electronic wire, cable, control cables, coaxial. We also design & fulfill custom & specialty cable needs thru our affiliate, DAVIS RF Co., div. of Orion Wire Co., Inc.

Thanks again, so much, for your business.

Steve Davis

Quality Workmanship in the USA